

Covet International 27 / 131 Hyde St Yarraville VIC 3013 t: +613 9398 8128 e: info@covet.com.au w: covet.com.au

Title:

Ever Art Wood® Mizotsuki Bolt Fix Batten System – Specification Guide

1 INSTRUCTIONS

The following is an example specification for Ever Art Wood Mizotsuki Bolt Fix Aluminum Batten System. Please note that the areas highlighted below require input based on the requirements of the project.



Tip:

To copy the specification from PDF, select the text and right click to copy. When pasting in the word document, right click and paste as Keep Text Only to keep the formatting.

2 PRODUCTS

2.1 Metal Batten Cladding

- A. Aluminium battens on mounting brackets.
- B. Manufacturer/ reference: Covet International/ Mizotsuki Ever Art Wood Bolt Fix Aluminium Batten System.
 - 1. Mounting bracket:
 - a) Type and material: Aluminium 'L' bracket.
 - b) Finish and colour: To match battens.***
 - 2. Battens:
 - a) Type and material: Aluminium extrusions.
 - b) Size: 20mm x 80mm/ 30mm x 50mm/ 30mm x 60mm/ 30mm x 75mm/ 30mm x 100mm/ 50mm x 50mm/ 40mm x 100mm/ 50mm x 100mm/ 60mm x 30mm.***
 - c) Spacing: 60mm/ 90mm/ 100mm/ 125mm/ 150mm/ 175mm/ 200mm/ Bespoke*** centre to centre.
 - d) Finish: Timber look.
 - e) Colour: Burakku Suchi-ru, Burakku Erumu, Chakooru Gurei, Kakicha, Kurocha, Daaku Pain, Burakku Eboni, Weebu Mahogani*, Buraun Eboni, Neikiddo Moku, Pain, Riigaru Oku, Kuri Masame, Biera Oku, Buraun Gurei, Kurashikku, Kareiro, Oku, Supuringu Oku*, Howaito Pain.***
 - 3. Fixing: Bolt and bracket fixed
- C. Additional information:
 - 1. Support framing: Concealed, suspended metal support framing.
 - 2. Insulation/ backing:***
 - a) Type: Acoustic backing.
 - b) Thickness: 7mm.
 - c) Colour: Black/ White.***
 - 3. Wall junction: Refer to the Design Drawings
- D. Performance requirements:
 - 1. NCC fire hazard classification:
 - a) Spread of flame index: 0.
 - b) Group: 1.
- E. Datasheet: https://www.covet.com.au/ever-art-wood-batten-mizotsuki
- F. Lead Time: 8-10 weeks.